

Very compact emergency power system for backup power supply 20 kVA Super soundproofed with Perkins

engine

Completion:

Generating Set: stationary **Gen Set:** silent Set

Technical Data Engine:

Engine Manufacturer:	Perkins	Engine Type:	404A-22G1
Engine No.:	in Produktion	Engine Power:	18,4 KW
Cooling:	water-cooled	Starting:	electrical 12 V DC
Rotation:	1500 rpm	Fuel:	heating oil EN 590

Technical Data Generator:

Generator Manufacturer:	Mecc Alte	Gen Set:	NPE32-2M/4C
Gen No.:	in Produktion	Gen Power:	20 kVA
Voltage:	400 / 231 Volt	Power Factor:	cos. - phi 0,8
Rotation:	1500 rpm		

Control Unit:

Setup:	automatic start	Functions:	Hand & Remotestart
Switch:	gen switch 4 pole	Delivery:	set up
Width ca. mm:		Depth ca. mm:	
Height ca. mm:			

Tank

Setup:	Baseframe fuel Tank with Bassin	Height ca. mm:	
Width ca. mm:		Capacity / Litre:	90
Depth ca. mm:			

Dimensions of unit:

Length ca. mm:	1.180	Height ca. mm:	1.650
Width ca. mm:	700	Weight ca. KG:	

Usage:

State:	new	year of manufacture:	2024
time of delivery:	ex work	Price plus VAT in 1/2:	on request:
Operating Hours:	1		
Location:	Verl - Germany		
Stock No:		Reserved:	nein / no

Delivery Contents:

Very compact emergency power system with a nominal power of 20 kVA PRP, can be used in a small space with only 56 dbA

4-cylinder Perkins industrial diesel engine with a displacement of 2.22 liters

Fuel consumption at 50% load 2.90 liters / hour
 Fuel consumption at 75% load 4.00 liters / hour
 Fuel consumption at 100% load 5.30 liters / hour
 Autonomy at 75% load ≈ 23 h

Type Lubricant Oil SAE 15W40
 Lubrication power l.* 10.60
 Type Coolant Antifreeze
 Coolant capacity l.* 12.50
 Suction filter paper cassette
 Battery capacity Ah 50
 Number of batteries* 1

Fuel system and energy balance

AC pump suction lift kPa 1
 Combustion air volume flow at LTP output (110%) 87 m³/h.
 Cooling air flow at LTP performance (110%) 2,412 m³/h.
 Exhaust flow at LTP performance (110%) 236.4 m³/h
 Exhaust gas temperature at LTP power (110%) 505.00 °C
 Max. exhaust back pressure kPa 10.20
 Exhaust heat at LTP power (110%) 16.60 kWt
 Energy on coolant at LTP power (110%) 19.60 kWt
 Radiant heat at LTP power (110%) 4.40 kWt

Control behind a protective flap
 With 4-pin circuit breaker
 Automatic control unit DSE4520, including:
 - Voltmeter, frequency meter, ammeter
 - Generator power display (kW, kV Ar, kV A & pf)
 - Hour meter
 - Tank content increase in %
 - Protection against overload (kW & kV Ar)
 - Low oil pressure protection with shut off
 - Protection device against high coolant temperature with shutdown
 - Protection against low fuel level
 - Malfunction on the alternator, battery charger
 - Protection device against overspeed (underfrequency)
 emergency button
 Terminal board for connection of the automatic switchboard

Very compact emergency power system for backup power supply 20 kVA Super soundproofed with Perkins

engine

battery charger
Main switch on/off

Product Images



